



-  EN1143-1
Burglary protection
-  EN15659
Fire protection (option)
-  VdS
Grade V
-  ECB-S
Grade V
+ LFS60P (option)
-  ISO
Class EN 5
-  DIN
4102 (light fire protection)



-  Domestic insurable
by arrangement
-  Commercial insurable
up to EUR 250.000

Fig. Safe EWS1000, hinge right
2 x K-Lock S+G adjustable each 1 key guide tube 2 bits, 2 shelves

Model	Outside dimensions			Inside dimensions			SH	Volume (l)	Weight (appr. kg)
	h	w	d (mm)	h	w	d (mm)			
EWS0849R	848	645	565	695	495	320	1	110	665
EWS0850R	848	810	725	695	660	480	1	220	935
EWS1000R	1003	810	725	850	660	480	2	269	1060
EWS1200R	1193	810	725	1040	660	480	2	329	1220
EWS1600R	1538	810	725	1385	660	480	3	439	1505
EWS1901R	1883	810	725	1730	660	480	4	548	1790
EWS1903R	1883	1110	725	1730	960	480	4	797	2230
EWS1902	1883	1110	725	1730	960	480	4	797	2270
EWS1904	1883	1415	725	1730	1265	480	4	1050	2720

SH = Shelf

Please add 60 mm to the listed outside depth for mountings.

[Safes]

[Type EWS]

EWS series safes are designed for total protection and offer Wertheim's usual level of high security. They are available with optional fire protection – tested and certified according to LFS60P. Safes weighing less than 1.000 kg must be anchored.

[Product information]

- Hinge** DIN right – model designation R (EWS1902, EWS1904 double-doored)
option: DIN left
- Door opening angle** 180°
- Body** double-walled, reinforced, filled with armoured, high resistant barrier material
- Door structure** triple-walled, reinforced, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
- Locking mechanism** three-way moving boltwork with large steel bolts, protected by glass plate with additional emergency re-locks, fix engaging steel bolts on the hinge side
- Anchoring** fitted for floor anchoring
anchoring bolts and shields are supplied for EWS0849, EWS0850
option: additional anchoring holes (customer specifies position)
- Alarm connection** VdS-certified cable channels to allow connection to a burglar alarm system
- Colour** outside RAL 7035 light grey + RAL 7045 tele grey1, inside RAL 7035 light grey
option: special colour according to RAL
- Lock** safes in grades IV and higher have to be equipped with at least 2 certified locks
any set of locks (from VdS class 2 up) is possible
- Equipment** shelf adjustable (height setting 69 mm, EWS0849 60 mm)
option: additional shelf, inside locker
option (from EWS0850 up): drawer, pull-out shelf
- Accessories** option: fire protection door rebate seals, alarm switch set, interior lighting
- Option** additional certified fire protection LFS60P – except models: EWS0849, EWS1902, EWS1904
bolted version (without fire protection) – assembly on site

[Equipment options]



EWS0849

EWS0850

EWS1000

EWS1200

EWS1600

EWS1901

EWS1903/1902

EWS1904