

## Deposit safes

EN 1143-2 Grade III

### Key features

- Designed to provide high-security deposit safety in retail outlets and service points
- Certified according to European Standard EN 1143-2 to Grade III
- Specially designed against manipulation
- Floor-anchoring for additional security against removal of the safe
- Limited access to contents of the safe – deposit customers have no access into the safe
- Standard colour light grey, RAL 7035
- Maximum deposit bag size: 45 mm (H) x 235 mm (W) x 155 mm (D)
- Right- or left-handed opening
- Rear- or front-facing deposit



### Options and fittings

- The safes can be equipped with electronic code locks or combination locks
- Option for two locks
- Deposit drawer keylock
- Kaso Cinema, camera-monitoring solution for user and deposit process verification
- Lockable compartments, shelves and other internal fittings



### Specifications

Model	PTK E3-310 DP	PTK E3-320 DP	PTK E3-330 DP
<b>External</b>			
Height (mm)	912	1262	1612
Width (mm)	634	634	634
Depth (mm)	550	550	550
<b>Internal</b>			
Height (mm)	493	843	1193
Width (mm)	486	486	486
Depth (mm)	364	364	364
Volume (l)	87	149	211
Weight (kg) Grade III	490	580	670
Deposit drawer height (from bottom)	762	1112	1462